



**MATERIAL SAFETY DATA SHEET  
 MAY BE USED TO COMPLY WITH OSHA'S HAZARD  
 COMMUNICATION STANDARD 29 CFR 1910, 1200.  
 STANDARD MUST BE CONSULTED FOR SPECIFIC REQUIREMENTS.**

**COMPANY: TURRET PUNCH COMPANY, INC.**

**MATERIAL: APPLIES TO ALL POLYURETHANES**

**SECTION 1: CHEMICAL PRODUCT / COMPANY IDENTIFICATION**

**MATERIAL IDENTIFICATION URETHANE**

**FLAMABILITY OF URETHANE IS A MINIMUM OF 600F**

**THIS MATERIAL WILL START TO MELT AT 450F BUT WILL SELF EXTINGUISH IF FLAME SOURCE IS REMOVED.**

**COMPANY IDENTIFICATION / MAILING ADDRESS:**

**7780 EDISON AVE  
 FONTANA, CA 92336**

**DATE PREPARED:**

**9/05/2011**

**COMPANY TELEPHONE NUMBER:**

**909-587-1820**

**TRANSPORT EMERGENCY TELEPHONE NUMBER**

**909-227-2034**

**MEDICAL EMERGENCY TELEPHONE NUMBER**

**909-227-2034**

**SECTION 2: COMPOSITION, INFORMATION ON INGREDIENTS**

<b>HAZARDOUS COMPONENTS 1% OR GREATER          CARCINOGENS 0.1% OR GREATER (SPECIFIC          CHEMICAL IDENTITY: COMMON NAME (S)</b>	<b>%(WT./VOL.)          (OPTIONAL)</b>	<b>CAS</b>	<b>OTHER LIMITS          RECOMMENDED PEL TLVS</b>			
<b>NONE</b>			<b>N/A</b>	<b>N/A</b>	<b>N/A</b>	<b>N/A</b>

**POLYURETHANE ELASTOMERS ARE FULLY REACTED POLYMERS FORMING ARTICLES WHICH ARE NOT  
 CONSIDERED HAZARDOUS UNDER OSHA'S CRITERIA 29 CFR 1910.1200. HOWEVER, HAZARDOUS DUSTS, VAPORS,  
 GASES, OR FUMES MAY BE RELEASED BY MECHANICAL OR THERMAL PROCESSING, OR BY THERMAL  
 DECOMPOSITION.**